

Pneumatic air operated press mod. AT-770/UP, utility legger shape.
Fast head movement and 60° head opening



Pneumatic air operated press,

head with live steam
and fast movement , adjustable squeezing pressure .
Pneumatic valves for steam distribution to both head and buck;
adjustable pedals for best confort .Buck with live steam
and vacuum (+ blowing on request). 60° head opening.
High professional press for high productivity .
Available either for connection to external steam , vacuum
and air supplies or self-contained.

Available extras :

Timer which allows control of all three phases of the finishing cycle .
Up-air facility on the buck with built-in vacuum unit
Sponging device with a selection between normal head closing
or spaced closing (2 or 3 cm).
Stainless steel sleeve arm and steam /air gun for spotting
Steam iron assembly
Anti-gloss plate

Technical Characteristics

Required power:	230V/1 or 400/3+N/50 Hz
Water feeding:	hosepipe ø 13 mm
Steam inlet:	1/2
Return outlet:	1/2
Air inlet:	3/8
Steam working pressure:	5 bar
Air working pressure:	7 bar
Steam consumption:	16÷20 Kg/h
Air consumption:	20 NL/MIN
Central vacuum connect.:	ø 48 mm
Vacuum depression:	200 mm H ² o
Vacuum air consumption:	360 m ³ /h
Boiler drain:	1/2
Vacuum outlet:	ø 100 mm
Boiler heating:	10÷12÷15÷18 KW
Iron heating element:	0.8 Kw
Vacuum motor:	0.37 Kw
Pump motor:	0.6 Kw
Compressor motor:	1,10 Kw
Encumbrance:	1300x1180 mm
Net weight :	360 Kg
Gross weight:	390 kg
Overall dimensions:	1400x1150x1400 mm

Primus Belgium
Driemasten 126
B-8560 Gullegem
Belgium

Tel.: +32(0)56 43 52 00
Fax: +32(0)56 40 34 63
E-mail: info@primuslaundry.com

Primus CE
Mistecka 1116
742 58 Pribor
Czech Republic

Tel.: +420 556 768 800
Fax: +420 556 723 383
E-mail: sales@primuslaundry.cz