



Pneumatic Press Mod. LV-800-BB Bosom Body shape with high grade nickel plated head.



Pneumatic press for LAUNDRYwith high grade

nickel plated polished head.

Bottom buck with pad and cover, both Steam heated, (not steaming, just heated).

Head closing by one or two buttons, or foot pedal + head safety guard.

Available either for connection to external steam and air supply or self-contained. .

Available extras:

Built-in 7 lts. electronic boiler- 8-10 KW Built-in 20 lts. electronic boiler -10-12-15-18 KW.

Water spray gun.

Adjustable head release timer.

Steam electric iron assembly GFV with swinging

iron support.

Technical Characteristics

230/1 o 400 V/.3+N50 required power 7or20lt boilers heating 8÷10 or 10÷12÷15÷18 KW

30 lt boiler heating Pump Motor

Vacuum Motor

compressor Motor

0,75 KW

Water feeding Hosepipe ø interno 12 mm 1/2"

0,6 Kw

1/2"

1/2"

3/8"

7 bar 7 bar

250 Kg

280 Kg

5÷8 bar

10÷12 Kg/h

Boiler drain Steam Inlet Return outlet

Steam working pressure Steam consumption

Air inlet

Air working pressure Air consumption

1040x1100 mm Encumbrance

Net weight with boiler Gross weight

Overall dimensions 1400x1150x1400 mm

Overall dimensions LAV/R1

Primus Belgium Driemasten 126 B-8560 Gullegem Belgium

+32(0)56 43 52 00 Tel.: +32(0)56 40 34 63 Fax: E-mail: info@primuslaundry.com

Primus CE Mistecka 1116 742 58 Pribor Czech Republic Tel.: +420 556 768 800 +420 556 723 383 E-mail: sales@primuslaundry.cz