

Pneumatic Press LV-800-F, mushroom shape with high grade nickel plated head



Pneumatic press for LAUNDRY with high grade nickel plated polished head .
 Bottom buck with pad and cover, both Steam heated, (not steaming just heated).
 Head closing by two buttons, or two buttons + head safety guard.
 Available either for connection to external steam and air supply or self-contained. .

Available extras :
 Built-in 7 lts. electronic boiler- 7-8-9-10 KW
 Built-in 20 lts. electronic boiler -10 or 12 KW.
 Water spray gun.
 Adjustable head release timer.
 Steam electric iron assembly GFV with swinging iron support.

Technical Characteristics

required power	230/1 o 400 V/.3+N50 Hz
7or20lt boilers heating	7 ÷ 10 or 10 ÷ 12 ÷ 15 ÷ 18 KW
30 lt boiler heating	
Pump Motor	0,6 Kw
Vacuum Motor	
compressor Motor	0,75 KW
Water feeding	Hosepipe ø interno 12 mm
Boiler drain	1/2"
Steam Inlet	1/2"
Return outlet	1/2"
Steam working pressure	5 ÷ 8 bar
Steam consumption	12 ÷ 14 Kg/h
Air inlet	3/8"
Air working pressure	7 bar
Air consumption	8 NL per cycle
Encumbrance	1250x1050 mm
Net weight with boiler	295 Kg
Gross weight	325 Kg
Overall dimensions	1400x1150x1400 mm
Overall dimensions LAV/R1	

Primus Belgium
 Driemasten 126
 B-8560 Gullegem
 Belgium

Tel.: +32(0)56 43 52 00
 Fax: +32(0)56 40 34 63
 E-mail: info@primuslaundry.com

Primus CE
 Mistecka 1116
 742 58 Pribor
 Czech Republic

Tel.: +420 556 768 800
 Fax: +420 556 723 383
 E-mail: sales@primuslaundry.cz