

Stainless steel Spotting table S-782



Professional steam **Spotting Table** ready for connection to central steam , vacuum and air supplies.

by pushing a pedal with a different pressure , gun releases three different type of steam : dry steam , moist steam and wet steam.

Compressed air is heated at an average temperature in order to fasten the drying process and avoid moisture and rings also on large areas of perspiration< br>

The main board and the swinging sleeve board are stainless steel

Available extras :

Built-in suction fan

Water spray gun

Cold spotting gun with accessories.

Technical Characteristics

Required power	230/400 V.3/50 Hz
Steam inlet	1/2"
Return outlet	1/2"
Steam working pressure	4 ÷ 6 bar
Steam consumption	5 ÷ 10 Kg /h
Air inlet	1/4"
Air working pressure	5÷7 bar
Air Consumption	150 NI /mm
Vacuum motor	0,25 Kw
Vacuum outlet	ø 100 mm
Central vacuum connect.	ø 70 mm
Vacuum depression	140 mm H ² o
Vacuum air consumption	300 m ³ /h
Compressor motor	
Board dimensions	900x300x160 mm
Arm dimensions	400x100x65 mm
Encumbrance	1530x520x910 mm
Net weight	122 Kg
Gross weight	152 Kg
Overall dimensions	1440x630x1100 mm
Volume	0.99 m ³

Primus Belgium
Driemasten 126
B-8560 Gullegem
Belgium

Tel.: +32(0)56 43 52 00
Fax: +32(0)56 40 34 63
E-mail: info@primuslaundry.com

Primus CE
Mistecka 1116
742 58 Pribor
Czech Republic

Tel.: +420 556 768 800
Fax: +420 556 723 383
E-mail: sales@primuslaundry.cz