

## Manual operated press Mod. ST-702-UL, utility shape board with polished head.



**Universal ironing Press** with stainless steel polished head, steam heated but not steaming and padded buck with live steam and vacuum. The movement of the upper head is operated by a pressure pedal, producing excellent results whilst being very easy to use and maintain. Available either for connection to external steam and vacuum supplies or self-contained. The built-in boiler can be powered to be connected to a second machine.

Available extras:

- Boiler
- Vacuum
- GFV iron assembly
- Sleeve spotting arm and shape.
- Anti-gloss Nomex cloth for head

---

### Technical Characteristics

---

Required power	220/380 V./1ø3/50 Hz
Water feeding	hosepipe ø 12 mm
Steam inlet	1/2"
Return outlet	v
Air inlet	
Steam working pressure	5 bar
Air working pressure	
Steam consumption	18÷20 Kg/h
Air consumption	
Central vacuum connect.	ø 100 mm
Vacuum depression	250 mm H <sup>2</sup> o
Vacuum air consumption	400 m <sup>3</sup> /h
Boiler drain	1/2"
Vacuum outlet	ø 100 mm
Boiler heating	10÷12÷15÷18 KW
Iron heating element	0,8 Kw
Vacuum motor	0,4 Kw
Pump motor	v
Compressor motor	
Encumbrance	1300x1100 mm
Net weight with boiler	370 Kg
Gross weight	430 Kg
Overall dimensions	1400x1150x1400 mm

---

Primus Belgium  
Driemasten 126  
B-8560 Gullegem  
Belgium

Tel.: +32(0)56 43 52 00  
Fax: +32(0)56 40 34 63  
E-mail: info@primuslaundry.com

Primus CE  
Mistecka 1116  
742 58 Pribor  
Czech Republic

Tel.: +420 556 768 800  
Fax: +420 556 723 383  
E-mail: sales@primuslaundry.cz